



M.A.P. system

Air Sealing & Seam Tape by Maxell

The primary and differentiating feature of Maxell Airtight Products(M.A.P.) and flashing materials is "Quick and easy to install".

Air Sealing & Seam Tape is a single-faced adhesive tape for fixing of vapor barrier to create a continuous air barrier and reduces moisture intrusion and accumulation into the wall system




Advantages

◆ Excellent Air-tightness

Physical Properties	Units	Results	2021 IECC Requirement
Air Permeability 5 specimens; @ $\Delta P=75\text{Pa}$	$\text{L}/(\text{s}\cdot\text{m}^2)$	0.0002	≤ 0.02
	cfm/ft^2	0.00003	≤ 0.004

Structure




Thickness : 6.7mil(0.17mm)

Complies with the 2021 IECC air permeance

Properties

Properties		Air Sealing & Flashing Tape
Adhesion	Vapor Barrier	5.3 lbf/in
	SUS	5.4 lbf/in
Air permeance		0.00003 cfm/ft ²

Properties



149° F/80%R.H×20weeks
 ≒ 20years in the U.S

※test conditions
 Storage temp. : 176° F
 Measured temp. : 77° F×50%R.H
 Peeling speed : 300mm/min
 Peeling angle : 180°

Fig. Adhesive Force After Leaving 149° F/80%R.H

Distributor : Interra USA, Inc. <http://www.interra-usa.com/>
 add: 900 SW 16th Street Suite 125, Renton, WA, 98057
 E-mail:info@interra-usa.com Tel:1-425-277-7850



Manufacturer : Maxell, Ltd. <https://biz.maxell.com/en/>
 Made in JAPAN

For more details, please visit our Website